















Rollable top lacquers for parquets and wooden floors

Kiilto offers a full range of products for installation and surface treatment of parquets and wooden floors: levelling compounds, adhesives, lacquers and cleaners.



Kiilto has extended its range of traditional floor lacquers with rollable top lacquers.

PRODUCT	PRODUCT DESCRIPTION	APPLICATION DRYING TIME	APPLICATION METHOD	COVERAGE	PACKAGE SIZE
Topaz 	Waterbased, 1-component top lacquer for domestic use. <ul style="list-style-type: none"> • very high resistance to wear • good rolling and levelling properties 	<ul style="list-style-type: none"> • 2 hours • light traffic after 24 – 48 hours • final strength after approx. 2 weeks 	 	8 - 10 m ² / l (1 application)	1 l ja 5 l <i>Semimatt 20</i> <i>Semigloss 55</i> <i>Gloss 75 (only 5 l)</i>
Amber 	Waterbased 1-component, lightly toning top lacquer for domestic spaces. <ul style="list-style-type: none"> • very high resistance to wear • good rolling and levelling properties 	<ul style="list-style-type: none"> • 2 hours • light traffic after 24 – 48 hours • final strength after approx. 2 weeks 	 	8 - 10 m ² / l (1 application)	5 l <i>Semimatt20</i> <i>Semigloss 55</i>
Opal 	Waterbased, 2-component top lacquer especially for public spaces, e.g. sport halls. <ul style="list-style-type: none"> • very high resistance to wear and heel marks • good rolling and levelling properties • both glosses meet DIN 18032-2 for slip resistance 	<ul style="list-style-type: none"> • 2 hours • light traffic after 24 – 48 hours • final strength after approx. 2 weeks 	 	8 - 10 m ² / l (1 application)	5 l (4,5 + 0,5) <i>Semimatt 20</i> <i>Semigloss 55</i>
Nature Matt 	Waterbased, 1-component, extra matt coating for wooden floors. Suitable for public and domestic spaces. <ul style="list-style-type: none"> • very high resistance to wear • good rolling and levelling properties • accentuates wood's natural appearance 	<ul style="list-style-type: none"> • 30 - 60 minutes (trowel application) • 2 - 4 hours (roller application) • light traffic after 48 hours • final strength after approx. 2 weeks 	 	25 m ² / l (1 trowel application) 6 - 8 m ² / l (1 roller application)	5 l <i>Extra matt 5</i>

KIILTO PRODUCT KIT FOR LACQUERED WOODEN FLOORS AND PARQUETS INCLUDE ALSO PRODUCTS FOR:

Preparation: **Start Primer**, Levelling compounds: **TopPlan DF** and **Fiberflex**

Gluing and filling: **Standard, Spezial, Solid, Slim, FlexSilan, Flex, Nopea Slim** and **Gap Parkettikitti** (parquet putty)

Priming: **Tempo, Smart** and **Urpo**

Lacquering: **Aku De Luxe, Kalle Pro**, and **Puulattialakka**

Cleaning: **Kiilto Kodinpuhdistaja** and **Kiilto Parkettipesu**